

食品排吸管 A1-002



应用:

食品罐车管, 针对散装物品运输罐车里的高温气体特殊设计(最高温度可达 +140℃)。适用于排吸各类流体食品, 如牛奶、葡萄酒、啤酒、果酒、果汁、苏打水、食醋、96% 浓度酒精等, 用于各类食品罐车装卸作业。

优点:

- 具有良好的柔韧性
- 罐车配套设计, 除压缩机设备连接外
- 光滑食品级内壁, 能有效抑制细菌滋生
- 外胶具有良好的耐老化、耐候性能
- 不含 phthalate(邻苯二甲酸酯)

技术参数:

- 内层: 食品级 EPDM 合成橡胶, 白色, 光滑
- 增强层: 高强度合成线绳加螺旋钢丝增强
- 外层: 抗老化 EPDM 合成橡胶, 蓝色, 表面布纹
- 工作温度: -30℃至 +100℃或 +140℃热空气

适用标准:

- EU 1935/2004
- FDA 21 CFR 177.2600
- 德国法规: BFR 建议第 11 款, 第二节
- 法国相应法规许可

Applications:

Particularly designed for additional air lines (temperature up to 140 ° C) on road tankers carrying bulk products. suction and discharge of liquid food-stuffs such as milk, wine, beer, cider, fruit juice, soda, vinegar and alcohol up to 96 %, with exception of fatty foodstuffs and oils, loading or unloading bays for road and rails tankers.

Advantages:

- Good flexibility and easy to handle.
- Suitable for road tankers equipment except compressor lines
- A smooth, seamless, white food grade tube that does not propagate bacterial growth
- Resistant to cleaning with detergents at temperatures up to + 140 ° C
- Cover with very good ageing and weather resistance
- Contains no phthalate

Technical description:

- Inner tube: food grade quality EPDM, white, smooth.
- Reinforcement: synthetic textile with embedded steel helix.
- Cover: weather resistant EPDM, blue, fabric impression.
- Temperature range: - 30 ° C to + 100 ° C, and + 140 ° C for additional air.

Standard/Approval:

- EU regulations n° 1935/2004 and 2023/2006.
- FDA regulation 21 CFR 177.2600.
- German legislation: BFR recommendation XXI cat. 2.
- French legislation.

食品排吸管 A1-002

产品编码	内径	外径	工作压力	爆破压力	耐负压	弯曲半径	重量	包装长度	
No.	in.	mm	mm	bar	bar	bar	mm	kg/m	m
A1-002-1000	1"	25.0	36.0	10	30	0.9	55	0.81	40
A1-002-1250	1-1/4"	32.0	43.0	10	30	0.9	70	0.98	40
A1-002-1500	1-1/2"	38.0	49.0	10	30	0.9	80	1.15	40
A1-002-1580	1-9/16"	40.0	51.0	10	30	0.9	85	1.20	40
A1-002-1690	*	43.0	54.0	10	30	0.9	92	1.30	40
A1-002-1770	*	45.0	56.0	10	30	0.9	98	1.32	40
A1-002-2000	2"	51.0	62.5	10	30	0.9	105	1.66	40
A1-002-2090	*	53.0	64.5	10	30	0.9	110	1.72	40
A1-002-2360	2-3/8"	60.0	71.5	10	30	0.9	125	1.85	40
A1-002-2500	2-1/2"	63.0	74.5	10	30	0.9	130	2.00	40
A1-002-2760	*	70.0	81.5	10	30	0.9	145	2.24	40
A1-002-3000	3"	76.0	88.5	10	30	0.9	165	2.95	40
A1-002-3500	3-1/8"	89.0	102.0	10	30	0.9	330	3.44	40
A1-002-3940	*	100.0	113.0	10	30	0.9	380	3.75	40
A1-002-4000	4"	102.0	115.0	10	30	0.9	400	3.80	40
A1-002-5000	5"	125.0	145.5	10	30	0.9	480	7.20	20
A1-002-6000	6"	150.0	171.5	10	30	0.9	570	8.80	20

blueFuture
您身边的工业专家