

# 食品级EDPM橡胶管

## A1-200

FOOD 10 HOT SD FDA



### 应用:

- 用于非脂肪和非油性食品物料的输送和抽吸。

### 技术参数:

- 内层: 食品级EPDM合成橡胶, 白色, 光滑
- 增强层: 合成纤维编织网并嵌入螺旋钢丝增强
- 外层: 耐老化合成橡胶, 蓝色布纹
- 工作温度: -30° C 至 +100° C

### 适用标准及认证:

- FDA

### Applications:

- Food suction and delivery hose excluding oily and fatty products.

### Technical description:

- Tube: Food grade EPDM synthetic rubber, white, smooth
- Reinforcement: Synthetic textile with embedded steel helix
- Cover: Weather resistant synthetic rubber, blue, fabric impression
- Temperature range: - 30 °C to + 100 °C

### Standard/Approval:

- FDA

| 产品编码        | 内径     |    | 外径 | 工作压力 | 爆破压力 | 真空度 | 弯曲半径 | 重量   | 长度 |
|-------------|--------|----|----|------|------|-----|------|------|----|
| No.         | in     | mm | mm | bar  | bar  | bar | mm   | kg/m | m  |
| A1-200-0750 | 3/4"   | 19 | 30 | 10   | 30   | 0.9 | 80   | 0.67 | 40 |
| A1-200-1000 | 1"     | 25 | 36 | 10   | 30   | 0.9 | 100  | 0.87 | 40 |
| A1-200-1500 | 1-1/2" | 38 | 50 | 10   | 30   | 0.9 | 160  | 1.2  | 40 |
| A1-200-2000 | 2"     | 51 | 64 | 10   | 30   | 0.9 | 200  | 1.65 | 40 |
| A1-200-2500 | 1-1/2" | 63 | 77 | 10   | 30   | 0.9 | 240  | 2.48 | 40 |
| A1-200-3000 | 3"     | 76 | 90 | 10   | 30   | 0.9 | 320  | 2.77 | 40 |

**blueFuture**  
您身边的工业专家