


## 食品清洗管 Blue Washing

Supflow BLUE WASHING With Micro



### 应用:

- 高品质的产品构造, 可用于食品加工厂、乳品间、包装车间、装瓶厂、啤酒厂、罐头厂和乳酪厂高达212°F (100°C) 的热水清洗作业

### 优点:

- 外胶具有超强耐磨和耐油性, 能够为抑制油品和动物脂肪的不良影响提供最大程度的保护
- 胶管外层种内嵌了抗菌保护材料
- 符合FDA要求的白色内管
- 很好的耐高温性能
- 不含塑化剂

### 技术参数:

- 内胶: 白色丁腈合成橡胶, 符合FDA
- 增强层: 螺旋合成纱线缠绕
- 外胶: 蓝色丁腈合成橡胶, 高耐油性并带有抗菌保护材料
- 工作温度: -20° F 至 212° F (-29° C 至 100° C)

### 适用标准及认证:

- FDA

### Applications:

- A high-quality construction for hot water up to 212°F (100°C) for cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries and creameries

### Advantages:

- Its super abrasion and oil-resistant cover provides maximum protection against the adverse effects of oil and animal fats
- The cover of Blue Washing hose incorporates antimicrobial built-in product protection
- The white tube is comprised of FDA-compliant materials
- Very good resistance to high temperature
- Phthalate free

### Technical description:

- Inner tube: White FDA-compliant NBR synthetic rubber
- Reinforcement: Spiral synthetic yarn
- Cover: Blue NBR synthetic rubber, High Oil Resistance with product protection
- Temperature Range: -20°F to 212°F (-29°C to 100°C)

### Standard/Approval:

- FDA

## 食品清洗管

## BLUE WASHING

产品编码 No.	内径 in	mm	外径 mm	工作压力 bar	爆破压力 bar	重量 kg/m	包装长度 m
Blue Washing-0375	3/8	9.5	17.5	20	80	0.30	152.4
Blue Washing-0500	1/2	12.7	22.8	20	80	0.45	152.4
Blue Washing-0625	5/8	15.8	26.9	20	80	0.62	152.4
Blue Washing-0750	3/4	19.1	30.2	20	80	0.65	152.4
Blue Washing-1000	1	25.4	38.1	20	80	0.95	137.16

blueFuture

您身边的工业专家