

高级食品管 ATLAS



应用:

- 轻质且非常柔韧的食品管，可用于食品物质如牛奶，饮料，酒类等的重力流、压力流和抽吸流的输送。

优点:

- 良好的柔性可满足小弯曲半径使用工况
- 白色光滑内胶符合FDA要求，防止细菌滋生
- 重量轻，方便安装及移动使用
- 适用温度范围广
- 不含塑化剂（邻苯二甲酸酯）

技术参数:

- 内胶：乙烯基丁腈橡胶，白色光滑（满足USDA和3-A标准要求）
- 增强层：合成纺织植物螺旋缠绕并带有2根镀锌防锈螺旋钢丝
- 外胶：乙烯基丁腈橡胶，灰色（波纹状，包裹压印）
- 工作温度：-25° F 至212° F (-32° C 至100° C)

适用标准及认证:

- FDA/USDA
- 3-A sanitary standard 18-03

Applications:

- A lightweight, highly flexible hose used for transferring food materials like milk, drinking etc. in gravity flow, pressure or suction service.

Advantages:

- Extremely flexible to accept the smallest bending radius without kinking
- White and smooth tube does not propagate bacterial growth and complies with FDA requirements
- Lightweight for easily installation and movement
- Change in temperature have little effect due to the qualities of the rubber compound
- Phthalate free

Technical description:

- Inner tube: White NBR synthetic rubber
- Reinforcement: Synthetic textile fabric plies and two galvanized wire helix
- Cover: Gray NBR synthetic rubber, corrugated, wrapped impression
- Temperature Range: -25°F to 212°F (-32°C to 100°C)

Standard/Approval:

- FDA/USDA
- 3-A sanitary standard 18-03

高级食品管 ATLAS

产品编码 No.	内径		外径 mm	工作压力 bar	爆破压力 bar	耐负压 bar	弯曲半径 mm	重量 kg/m	包装长度 m
	in	mm							
ATLAS-0750	3/4	19.1	29.4	10.3	40	0.9	45	0.62	60.96
ATLAS-1000	1	25.4	35.7	10.3	40	0.9	50	0.79	60.96
ATLAS-1250	1-1/4	31.8	44.0	10.3	40	0.9	60	0.95	60.96
ATLAS-1500	1-1/2	38.1	48.8	10.3	40	0.9	64	1.15	60.96
ATLAS-2000	2	50.8	62.0	10.3	40	0.9	76	1.49	60.96
ATLAS-2500	2-1/2	63.5	76.2	10.3	40	0.9	127	2.17	60.96
ATLAS-3000	3	76.2	89.2	10.3	40	0.9	140	2.90	60.96
ATLAS-4000	4	101.6	115.6	10.3	40	0.9	191	3.85	60.96
ATLAS-5000	5	127.0	143.8	10.3	40	0.9	305	5.71	30.48
ATLAS-6000	6	152.4	169.2	10.3	40	0.9	432	6.77	30.48
ATLAS-8000	8	203.4	224.4	10.3	40	0.9	1016	12.75	30.48

blueFuture

您身边的工业专家